

| | Type | L # | Hits | Search Text | DBs | Time Stamp | Comments | Error or Definition | Errors |
|---|------|-----|-------|---|----------|------------------|----------|---------------------|--------|
| 1 | BRS | L5 | 49 | ("4377789" "5442318" "5859566" "5936466" "4783602" "5245579" "5323120" "5491447" "5729178" "5914638" "6329849" "6369743" "6396137" "6407658" "6426676" "6714079" "5408235" "6362688" "4823092" "5386200" "5568561" "5661754" "5673221" "5714906" "6163466" "4295088" "4300091" "4342013" "4420726" "4524246" "4885477" "4907121" "5321575" "5632280" "5856757" "5963084" "5990743" "6009000" "6075406" "6081133" "6084452" "6107882" "6225837" "6225837" "6247075" "4272728" "4287392" "4296382" "4365210" "4371844") .pn. | USPAT | 2005/08/24 17:29 | | | |
| 2 | IS&R | L1 | 5 | (("6298226") or ("5408497") or ("5936466") or ("5491447") or ("5281924")) .PN. | USPAT | 2005/08/24 17:28 | | | |
| 3 | IS&R | L4 | 1 | ("20020118061") .PN. | US-PGPUB | 2005/08/24 17:29 | | | |
| 4 | BRS | L6 | 15671 | common near2 mode | USPAT | 2005/08/24 17:53 | | | |
| 5 | BRS | L7 | 278 | (common near2 mode) near2 voltage\$ near2 (detect\$ or sens\$) | USPAT | 2005/08/24 19:37 | | | |

| | Type | L# | Hits | Search Text | DBs | Time Stamp | Comments | Error or Definition | Errors |
|----|------|-----|--------|---|---|------------------|----------|---------------------|--------|
| 6 | BRS | L8 | 33359 | differential near2 output\$ | USPAT | 2005/08/24 19:38 | | | |
| 7 | BRS | L9 | 9430 | transconduct\$ | USPAT | 2005/08/24 19:38 | | | |
| 8 | BRS | L10 | 89138 | reference near2 voltage\$ | USPAT | 2005/08/24 19:42 | | | |
| 9 | BRS | L11 | 42 | 7 and 8 and 9 and 10 | USPAT | 2005/08/24 17:52 | | | |
| 10 | BRS | L12 | 650116 | common near2 mode voltage\$ | USPAT | 2005/08/24 17:53 | | | |
| 11 | BRS | L13 | 42 | 11 and 12 | USPAT | 2005/08/24 19:26 | | | |
| 12 | BRS | L14 | 5 | 1 and 10 | USPAT | 2005/08/24 19:30 | | | |
| 13 | BRS | L15 | 5 | 5 and 7 and 10 | USPAT | 2005/08/24 19:34 | | | |
| 14 | BRS | L16 | 513 | 330/258.ccls. | USPAT | 2005/08/24 19:35 | | | |
| 15 | BRS | L17 | 669 | 330/260.ccls. | USPAT | 2005/08/24 19:35 | | | |
| 16 | BRS | L18 | 130 | (common near2 mode) near2 voltage near2 (detect or detecting or detector or sense or sensing or sensor) | US-PGPUB; USOCR; EPO; JPO; DERWENT; IBM_TDB | 2005/08/24 19:38 | | | |

| | Type | L# | Hits | Search Text | DBs | Time Stamp | Comments | Error Definition | Errors |
|----|------|---------|--------|---|---|----------------------|----------|------------------|--------|
| 17 | BRS | L1 9 | 30787 | differential near2 (output or outputs) | US-PGPUB; USOCR; EPO; JPO; DERWENT; IBM_TDB | 2005/08/ 24 19:38 | | | |
| 18 | BRS | L2 0 | 7036 | transconductance or transconductor or transconductors | US-PGPUB; USOCR; EPO; JPO; DERWENT; IBM_TDB | 2005/08/ 24 19:42 | | | |
| 19 | BRS | L2 1 | 111365 | reference near2 (voltage or voltages) | US-PGPUB; USOCR; EPO; JPO; DERWENT; IBM_TDB | 2005/08/ 24 19:42 | | | |
| 20 | BRS | L2 2 | 9 | 18 and 19 and 20 and 21 | US-PGPUB; USOCR; EPO; JPO; DERWENT; IBM_TDB | 2005/08/ 24 19:43 | | | |